

Software Information Sheet



JCM American Corporation
 Japan Cash Machine Germany GmbH
 JCM Gold (H.K.) Ltd.
 JCM United Kingdom Ltd.
 Japan Cash Machine Co., Ltd. (Headquarters – Japan)

TEL +1-702-651-0000
 TEL +49-211-530645-0
 TEL +852-2429-7187
 TEL +44-870-770-2863
 TEL +81-6-6703-8405

General Information

Model Name:	EBA-21-SD2			SW.Reg. No.:	G08-088			
SW. Name:	EBA-21(CZE5)-SD2 ID-003			Date: (dd.mm.yyyy)	10.07.2008	Rev:	A1	
SW. Version:	V4.04-05			Note:				
Country (Code):	Czech Republic(CZE)			Guide:	None			
Currency:	Koruna			Check Sum:	F40C			
Direction:	4Way			CRC (seed= 0000):	08C4			
Denomination: Years & MRI III/IV.2007 Ident # 64/65th Edition	Denomination	Printed	Issued	MRI#	Denomination	Printed	Issued	MRI#
	50	'94		CZK50.1	1000	'96		CZK1000.1B
	100	'93		CZK100.1A	1000	'08		
	100	'95'97		CZK100.1B/C	2000	'96		CZK2000.1
	200	'93		CZK200.1A	2000	'99		CZK2000.1B
	200	'96'98		CZK200.1B/C	2000	'07		
	500	'93		CZK200.1A	5000	'99		CZK5000.1B
	500	'95'97		CZK500.1B/C				
Acceptance Rate:	No less than 90%							
Security level:	Low							
EPROM:	2 Mbit 90 nano-second data access or faster. ST Part M27C2001-90 or equivalent.							
Modifications:	V4.03-05 -> V4.04-05							
Validation:	Acceptance for 1000 ('08) Korun added.							
Operation:								
Interface:								
Memo:								

Dip Switch Settings

1	OFF	Normal operation mode
	ON	Test and adjustment mode
2	OFF	Acceptor only
	ON	With SD2 Unit
3	OFF	Not assigned
	ON	Not assigned
4	OFF	50 Accept
	ON	50 Reject
5	OFF	100 Accept
	ON	100 Reject
6	OFF	200 Accept
	ON	200 Reject
7	OFF	500/1000 Accept
	ON	500/1000 Reject
8	OFF	2000/5000 Accept
	ON	2000/5000 Reject

ID-003 Data Settings specification

VERSION DATA

Version	E(CZE5)-21-SD2 ID003-05v404-05 10JUL08 08C4
---------	---

ESCROW DATA

Code	Denomination
61h	Reserved
62h	Reserved
63h	50
64h	100
65h	200
66h	500
67h	1000
68h	2000
69h	5000

CURRENCY ASSIGN DATA

Code	Country	Value	Exponent
61h	00h	00h	00h
62h	00h	00h	00h
63h	2Ch	05h	01h
64h	2Ch	0Ah	01h
65h	2Ch	14h	01h
66h	2Ch	32h	01h
67h	2Ch	64h	01h
68h	2Ch	C8h	01h
69h	2Ch	32h	02h

ENABLE/DISABLE DATA

Bit	Data 1	Data 2
0	Reserved	5000
1	Reserved	Reserved
2	50	Reserved
3	100	Reserved
4	200	Reserved
5	500	Reserved
6	1000	Reserved
7	2000	Reserved



0: Enable 1: Disable (Default: **03FEh**)

SECURITY DATA

Bit	Data 1	Data 2
0	Reserved	5000
1	Reserved	Reserved
2	50	Reserved
3	100	Reserved
4	200	Reserved
5	500	Reserved
6	1000	Reserved
7	2000	Reserved

0: Normal 1: Security Level high (Default: **0000h**)

DIRECTION DATA

Bit	Direction	Example: 100 Korun	
0	A		B
1	B		
2	C		
3	D		
4	Not used		D
5	Not used		
6	Not used		
7	Not used		

0: Not Inhibit 1: Inhibit (Default: **00h**)

OPTIONAL FUNCTION DATA

Bit	Data 1	Data 2
0	Hanging Function [01]	Not used
1	Not used	Not used
2	Not used	Not used
3	Not used	Not used
4	Not used	Not used
5	Not used	Not used
6	Not used	Not used
7	Not used	Not used

0: Disable 1: Enable (Default: **0000h**)

[01]Hanging Function

Rejection of the bill is completed with the end of the bill kept remaining in the acceptor.
(To prevent dropping of the bill)